

Declaration of Performance No. DOP_B0015

ABLOY LOCK CASE

Manufacturer:

Abloy Oy
Björkboda factory
 Konttorintie 2
 FI-25860 Björkboda
 FINLAND

ABLOY® 4262

Intended use of the construction product:

Lock case for interior fire door.

System or systems of assessment and verification of constancy of performance of the construction product: AVCP 1

NOTIFIED PRODUCT CERTIFICATION BODY:


VTT Expert Services Ltd
ID No. 0809
 PO Box 1001
 FI-02044 VTT
 FINLAND

Category of use	3	High chance of misuse, e.g. doors in public buildings	EN12209:2003 Building hardware - Mechanically operated locks, latches and locking plates
Durability and load on latch bolt	X	200 000 test cycles	
Door mass and closing force	7	Up to 100 kg door mass	
Suitability for use on fire/smoke doors	1	Suitable for use on fire/smoke resisting door	
Safety	0	No safety requirement	
Corrosion resistance and temperature	F	High corrosion resistance, from -20 °C to +80 °C	
Security and drill resistance	1	Minimum security and no drill resistance	
Field of door application	H	Mortice lock for hinged door	
Type of key operation and locking	C	Lever lock, manually locking	
Type of spindle operation	2	Unsprung lever handle	
Key identification	0	No requirements	

Notified product certification body performed the determination of the product type on the basis of type testing (including sampling), initial inspection of the manufacturing plant and of the factory production control and continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance of the product.

No. 0809-CPD-0557

Björkboda, 28-June-2013


 Jouni Haapaniemi, Vice President
 Abloy Oy, Lock Cases