

## ABLOY HANDLE TYPE

### MANUFACTURER:

**Abloy Oy**  
**Joensuu factory**  
Wahlforssinkatu 20  
FI-80100 Joensuu  
FINLAND

System or systems of  
assessment and verification  
of constancy of  
performance of the  
construction product:  
AVCP 1

### NOTIFIED PRODUCT CERTIFICATION BODY:

**VTT Expert Services Ltd**  
**ID No: 0809**  
P.O.Box 1001  
FI-02044 VTT  
FINLAND

Notified product certification  
body performed the  
determination of the  
product type on the basis of  
type testing (including  
sampling), initial inspection  
of the manufacturing plant  
and of the factory  
production control and  
continuous surveillance,  
assessment and evaluation  
of factory production control  
and issued the certificate of  
constancy of performance  
of the product.

0809-CPD-0764

<b>ABLOY FORUM 4</b>	<b>EH004</b>
<b>ABLOY POLAR 6</b>	<b>EH006</b>
<b>ABLOY STRATO 13</b>	<b>EH013</b>
<b>ABLOY PRESTO 3-20</b>	<b>EH060</b>
<b>ABLOY INOXI 3-19</b>	<b>EH070</b>
<b>ABLOY INOXI 3-19k</b>	<b>EH073</b>

### Approved plate types:

032  
030  
0321  
0650  
0630  
0651


### Description:

Door handle

### Intended use or uses of the construction product:

On EN179 EXIT doors  
On fire and smoke compartmentation doors

Category of use	3	High frequency of use	EN179:2008
Durability	7	200 000 cycles	
Door mass	6	up to 200kg	
Suitability for use on fire/smoke door	B	Suitable on fire doors	
Safety	1	Grade1, only one grade	
Corrosion resistance	3	96h	
Security	4	3000N	
Projection of operating element	2	Standard projection	
Type of operation	A	Lever handle operation	
Field of door application	A	Outwardly opening single/double door: active or inactive leaf	



27.06.2013 Abloy Oy  
Jaakko Meriläinen  
Vice President  
Architectural Hardware